

RGBlink[®]



AV Conference Integrated Solution

RGB10X-MEET-BK

A perfect combination to provide smooth and natural audio and video effects for participants, providing comfortable, pleasant and immersive experience for small and medium-sized remote conference applications.



Key Features

- 10X high-definition optical zoom lens
- Wireless Bluetooth omnidirectional speakerphone
- Plug and Play, USB-A/USB-C input interface to achieve high compatibility with computers
- A perfect combination to stream to Youtube ,facebook, Twitter, Tik Tok, bilibili and other platforms
- Easy access to Tencent Meeting, DingTalk Meeting, ZOOM, Feishu Meetings to realize high-definition audio and video conference
- Quick AV pick-up via Vmix and OBS, excellent companion for your live studio

AV Conference Integrated Solution



USB PTZ Camera with
10X Optical Zoom × 1

Omnidirectional
Speakerphone × 1

USB Hub × 1

Specification

RGB10X-USB-BI USB PTZ Camera with 10X Optical Zoom

Connectors	Video (Output)	USB 2.0	1xUSB-A
	Communication	RS232	2xDIN 8
		RS485	1x2 Pin Terminal Connector
	Power		1xHEC3800 DC Socket
Performance	Camera	Optical Zoom	10X f = 4.34 ~ 41.66mm
		View Angle	8.8° ~ 70°
		AV	F1.85 ~ F2.43
		Digital Zoom	10X
		Minimum Illumination	0.5Lux (F1.8, AGC ON)
		DNR	2D & 3D DNR
		White Balance	Auto/Manual/One Push/3000K/3500K/4000K/4500K/5000K/5500K/6000K/6500K/7000K
		Focus	Auto/Manual/One Push
		Exposure	Auto/Manual
		BLC	ON/OFF
	Video Adjustment	Brightness/Color/Saturation/Contrast/Sharpness/B/W mode/Gamma curve	
	SNR	>55dB	
	Effective Pixels	2.07m,16:9	
Pan-and-Tilt Parameter	Pan/Tilt Movement	-170° ~ +170°/-30° ~ +90°	
	Pan/Tilt Control Speed	0.1 ~ 60°/S; 0.1 ~ 30°/S	
	Preset Speed/Quantity	Pan:60°/S, Tilt:30°/S; Up to 255 preset positions (10 remote control)	
Video Compression Format	MJPEG H.264 H.265		
Output Resolutions	720p@25/30 1080p@25/30		
Control Protocol	VISCA Pelco-D Pelco-P		
Operating System	Windows 7 Windows8 Windows10 Mac osx Linux		
USB Communication Protocol	UVC		
Power	Input Voltage	DC12V/0.25A	
	Max Power	2.5W	
Working Environment	Temperature	-10°C ~ 50°C	
	Humidity	20% ~ 80%	
Physical	Net Weight	1kg	
	Net Dimension	156.8mm×112.6mm×139.5mm	

USB-Hub

Connectors	Output	USB 3.0	4×USB-A
	Input	USB 3.0	1×USB-C
		USB 3.0	1×USB-A
	Power	USB	1×Micro USB
USB		1×USB-C	
Performance	Supported Systems	Windows Linux MAC OS	
	Indicator	Blue LED Indicator	
Power	Power Consumption	29mA (No Load)	
Environment	Working Temperature	0°C ~ 45°C	
	Storage Temperature	-10°C ~ 60°C	
Physical	Dimension	Net 76mm x 50.5mm x 20mm (L * W * H)	

RGB3X-6MIC-BT Omnidirectional Speakerphone

Connector	USB 2.0	1×USB-A	
Performance	Microphone	Type	6×MEMS Microphone
		Sensitivity	-42dB re. 1V/Pa
		SNR	59dB
		Pick-up Diameter	2 m
	Speakerphone	Output Power (MAX.)	7W
		Sensitivity	82dB SPL +/-3dB SPL @1m, 1W
	Battery	Model	2450mAh
		Charging Power	5V/1A
		Duration	12 hours
		Standby	450 days
	USB Cable	0.9m	
Bluetooth	Yes (30 m)		
Connection	USB 2.0 PNP Bluetooth		
Power Supply	USB/Li-Po		
Physical	Net Dimension	Φ132.5mm x 35.5 mm	
	Net Weight	320g	

Order Code

Product Code	Item
981-0011-17-0	RGB10X-MEET-BK AV Conference Integrated Solution

Contact us

Tel: +86-592-5771197

Fax: +86-592-5788216

E-mail: sales@rgbink.com

Headquarter: Room 601A, No. 37-3 Banshang community, Building 3, Xinke Plaza,
Torch Hi-Tech Industrial Development Zone, Xiamen, China

RGBlink[®]

www.rgbink.com

