

## Product and Technical News in February 2020

### XPOSE

#### Version V2.0.2.42

##### ● Update

- 1、 Increase Hot-Key list in Display Management;
- 2、 Increase select multi-display areas and Scale, Remove, Delete at the same time function.;
- 3、 Increase Layer Preview function.;
- 4、 Add extend Preview picture, to offer IP streaming preview on PST, PGM, SIGNAL function;

#### For Subito-S4:

- 1、 Add loading off-line Scrip function;
- 2、 Add IP Reset option in Factory Reset;

##### ● Optimization

- 1、 Optimize all the user interface of XPOSE2.0;
- 2、 Optimize the option for Image quality as below: High-Quality, Normal, Smooth;
- 3、 Optimize the output resolution part, system revise the refresh rate only and will not delete the display area or display that has be set before;
- 4、 Optimized the Format Range setting on output module, with Module and All option.;

#### For Subito-S4:

- 1、 Optimized the LED parameter setting abnormally problem on Display Management;

#### For GX4:

- 1、 Optimized the LED parameter setting abnormally problem on Display Management.;

#### For FLEXP8:

- 1、 Display 2,4,6 and 8 of Flexpro8 can support up to 8 layer each port.

**Noted: When use XPOSE V2.0.2.42 to control those devices, the firmware version of device are required as below:**

Address: S601 Weiye Building Torch Hi-Tech Industrial Development Zone Xiamen,Fujian P.R.C

Tel: 4008 592 315

Fax: +86 592 5788216

Email: support@rgbblink.com <http://www.rgbblink.com>

X2: V3.03 (presentation application);

X3\_X3p: V3.62;

X7: V3.49;

X14: V1.13;

D4: V3.71 (presentation application,);

D6: V3.03 (presentation application);

Subito-S4: V1.07;

GX4: V1.83

- **Obtain latest firmware download IP address**

Pls contact RGBLINK sales team or customer service personnel for it.