

MSP 530
HDMI 2.0 to HDBaseT 3.0 Extender Set



Key Features

- HDCP 2.X
- Transfer uncompressed 4K HDMI signals up to 70m by CAT6 or above category cable
- Support 4K@60 4:4:4 Dolby Vision
- Support PoH / PoE
- Bi-directional IR
- Support KVM
- Zero latency




Specification

Connectors	Input	TX	HDMI 2.0 In/OUT	2×HDMI Type A
		RX	HDBaseT	1×RJ45
	Output	TX	HDBaseT	1×RJ45
		RX	HDMI 2.0 In/OUT	2×HDMI Type A
	Communication	TX	USB	1×USB-A (KVM)
			Update	1×USB-B
			IR (IN Out)	2×3.5mm Phone Jack
			LAN	1×RJ45
		RX	CONFIG	1×RJ45
			USB	1×USB-A (KVM)
Update			1×USB-B	
IR (IN Out)			2×3.5mm Phone Jack	
Power	TX	LAN	1×RJ45	
		CONFIG	1×RJ45	
Performance	Input Resolutions	TX	HDMI HDBaseT	
		SMPTE	720p@23.98/24/25/29.97/30/50/59.94/60 1080i@23.98/24/25/29.97/30/50/59.94/60 1080p@23.98/24/25/29.97/30/50/59.94/60 2160p@25/29.97/30/50/60	
		VESA	800×600@60 1024×768@60 1280×768@60 1280×1024@60 1366×768@60 1600×1200@60 1920×1080@60 2048×1152@60 2560×1600@60 3840×1080@60 2880×2340@50/60 3584×2048@60 3840×1080@60 3840×2160@60 4096×2160@60	
	Output Resolutions	TX	HDMI HDBaseT	
		SMPTE	720p@23.98/24/25/29.97/30/50/59.94/60 1080i@23.98/24/25/29.97/30/50/59.94/60 1080p@23.98/24/25/29.97/30/50/59.94/60 2160p@25/29.97/30/50/60	
		VESA	800×600@60 1024×768@60 1280×768@60 1280×1024@60 1366×768@60 1600×1200@60 1920×1080@60 2048×1152@60 2560×1600@60 3840×1080@60 2880×2340@50/60 3584×2048@60 3840×1080@60 3840×2160@60 4096×2160@60	
	PoE Max	TX	125mA	
	Supported Standard	TX	HDMI 2.0	
RX		HDBaseT 3.0 3.0		
Enviroment	Working Temperature	TX	0 ~55 ℃	
	Humidity	TX	0~65%	
Physical	Weight	Net(Device)	0.5 kg (TX/RX)	
	Dimensions	Net(Device)	166mm×111.5mm×36mm (TX/RX)	

Application



Dimensions



MSP 530 TX | RX

Order Codes

Product Code	Item
611-0530-00-0	MSP 530 Set
611-0530-01-0	MSP 530 TX
611-0530-02-0	MSP 530 RX

