

4K Ultra HD PTZ Camera



Key Features

- 4K Ultra HD Image, with resolution up to 4K@60fps
- 12x optical zoom lens, with 80.4° FOV without distortion
- Fast, accurate and stable auto focus
- Low Noise and High SNR
- 4K output through LAN, HDMI and USB 3.0
- Multiple Audio/Video Compression Standard
- Multiple Control port and control protocol
- Multiple Network Protocol include RTMP,RTP,VISCA

Specification


Connectors	Video(Output)	HDMI	1×HDMI-A
		USB3.0	1×USB-B
		LAN	1×RJ45
	Audio	Input	1×3.5mm Stereo Jack
	Communication	RS232 In/Out	2×DIN 8
		RS422 (RS485)	1×4Pin Terminal
Performance	Camera	Optical Zoom	12X
		Focus	f=3.85 mm ~ 43.06 mm ±5%
		View Angle	Horizontal: 7.59° (tele) ~80.4° (wide) Tilt:4.6° (tele) ~50.0° (wide)
		Effective Pixels	8.51m,16:9
		Aperture	F1.8 ~ F3.56±5%
		Minimum Illumination	0.05 lux (F1.8, AGC ON)
		DNR	2D & 3D DNR
		White Balance	Auto / Manual/ One Push/ Specified color temperature
		Focus Mode	Auto / Manual/ One Push
		Explosure Mode	Auto / Manual / Shutter Priority / Iris Priority / Whiteness Priority
		Shutter Speed	1/25~1/10000
	Dynamic range	OFF/ Dynamic level adjustment	
	BLC	ON/OFF	
	Video Adjustment	Brightness/Color/Saturation/Contrast/Sharpness/B/W mode/Gamma curve	
	SNR	≥50dB	
	Pan-and-Tilt Parameter	Pan/Tilt Rotation	-110°~+110°/-30°- +30°
		Pan/Tilt Control Speed	0.1~100°/S ; 0.1~70°/S
Preset Speed/Numbers		Pan:100°/S, Tilt:70°/S; Up to 255 preset positions (10 remote control)	
Audio Compression Format	AAC,MP3,G.711A		
Video Compression Format	LAN:H.264, H.265	USB3.0: MGPG, H.264, YUY2, NV12	
Output Resolutions	HDMI	720p@50/60 1080i@50/60 1080p@25/30/50/60 2160p@25/30/50/60	
	SMPTE		
	USB 3.0		
	YUY2/NV12	320×176@25/30 640×360@25/30 640×480@25/30 960 ×540@25/30 1280×720@25/30 1920×1080@25/30	
MJPEG/H.264/H.265	320×176@25/30 640×360@25/30 640×480@25/30 960 ×540@25/30 1280×720@25/30 1920×1080@25/30 3840×2160@25/30		
Control Protocol	VISCA Pelco-D Pelco-P		
Baud Rate(bps)	115200 9600 4800 2400bps		
Network Protocol	RTSP RTMP ONVIF GB/T28181 VISCA		
Power	Input Voltage	DC12V	
	Max Power	18W	
Environment	Temperature	-10℃~50℃	
	Humidity	20%~80%	
Physical	Weight	Net	1.7kg
		Package	3.5kg
	Dimension	Net	220mm×144mm×159mm
Package		275mm×260mm×350mm	

Order Codes

Product Code	Model
981-0011-09-0	RGB12X-UHD-WH 4K Ultra HD PTZ Camera

* There is no standard bracket for this PTZ. If necessary, please contact RGBlink sales for additional orders.

Dimension



Tel: +86-592-5771197 | Fax: +86-592-5788216 | E-mail: sales@rgbink.com

Headquarter: S601 Weiye Building, Torch Hi-Tech Development Zone, Xiamen, Fujian, P.R.C.

Specifications are correct at time of printing and subject to change or alteration without notice.

RGBlink
www.rgbink.com

