

Specification

Connectors	Input	HDMI 1.3	2×HDMI-A
		USB 3.0	2×USB TypeA
	Output	HDMI 2.0	1×HDMI-A
	Record	USB 2.0	1×USB TypeA
	Audio	In	1×3.5mm Audio Jack
		Out	1×3.5mm Audio Jack
	Communication/Stream	LAN	1×RJ45
Performance	Power		1×USB-C
	Input Resolutions	HDMI	
		SMPTE	720p@50/60 1080p@23/24/60
		VESA	1024×768@60 1280×720@60 1280×800@60 1280×1024@60 1360×768@60 1600×1200@60 1680×1050@60 1920×1080@60
	Output Resolutions	HDMI	
		SMPTE	720p@50/60 1080p@24/25/50/60 2160p@60
		VESA	1024×768@60 1280×720@50/60 1280×800@60 1280×1024@60 1360×768@60 1920×1080@50/60 3840×2160@60
Screen Feature	Supported Standard	HDMI	1.3(in) 2.0(out)
		USB	3.0
	Screen Dimension	5.5 "TFT	
	Resolution	1080×1920 pixels	
	Dot Pitch	0.063(H)×0.021(W)(mm)	
	Aspect Ratio	16:9	
	Brightness	450cd/m²	
Power	Contrast	1000:1	
	Backlight	LED	
	View Angle	80°/80°(L/R)80°/80°(U/D)	
Environment	Input Voltage	9V/2A	
	Max Power	18W	
Physical	Temperature	0°C ~ 55°C	
	Humidity	5%~85%	
Order Codes	Weight	Net	350g(without battery);882g(with battery)
		Package	770g
	Dimension	Net	161mm×106mm×36mm
		Package	255mm×145mm×85mm
Order Codes	Product Code	410-5513-01-0	TAO 1 pro
		490-5513-01-0	TAO 1 pro lithium battery(optional)








Talent Anchor Online



Dimension



Proudly designed and manufactured in Xiamen Hi Technology Zone, China
WEB: www.rgblink.com EMAIL: sales@rgblink.com PHONE: +86 592 5771197



www.rgblink.com



TAO 1pro is a Broadcasting streaming decoder with a 5.5 inch FHD preview display, but also a 4 channels seamless video switcher for 2 USB 3.0 and 2 HDMI 1.3 inputs, and supports streaming directly by ethernet output which is ready to connect to external cloud based router and streaming from Anywhere to Everywhere.

TAO 1pro is compatible with standard USB 2.0 and USB 3.0 cameras by UVC protocol, and brings itself as a much affordable and user friendly streaming tools for anybody, the talents who is willing to be Anchor Online.

TAO 1pro is also with touch panel for finger configuration, and with optional 2 chargeable battery extending its capacity for outdoor application.

Scene 1: Seamless switching between USB and HDMI inputs



Scene 2: Seamless switching between different USB inputs



TAO 1pro

Talent Anchor Online



Key Features

- 5.5-inch touchscreen operation
- Fast image processing
- video monitoring
- Dual battery Options
- Recording via USB 2.0 port
- Multistream up to 4 Live Streaming platform Simultaneously
- USB and HDMI signal multicasting
- Bluetooth 5.0
- Extending Monitor
- NDI5.0 Encoder

Scene 3: Ready for Bluetooth remote control



Scene 4: Input preview and extending monitor (90° supported)



Scene 5: Outdoor wireless streaming

