

PTZ Camera



Front View



Rear View



Left View

Key Features

- High speed optical zoom
- High performance in low light scenarios with Wide Dynamic Range
- Full 1920×1080p HD Resolutions up to 60 frames per second
- H.265/H.264 Dual Stream Output Adapted to Different Network Environments
- Pan and Tilt Control
- Optional interface
- Optional 12X/20X/30X optical zoom
- Wide Application
- Low-power Sleep Function

Specification

Performance	Camera	12X	20X	30X
		Optical Zoom	f=4.1~49.2mm	f=5.05~91.50mm
View Angle	6.57°~70.28°	3.45°~60.04°	2.14°~58.1°	
AV	F1.8~F2.68	F1.8~F2.9	F1.3~F4.8	
Digital Zoom	10X			
Minimum Illumination	0.5Lux (F1.8, AGC ON)			
DNR	2D & 3D DNR			
White Balance	Auto/Manual/One Push/3000K/3500K/4000K/4500K/5000K/5500K/6000K/6500K/7000K			
Focus	Auto/Manual			
Aperture/Electronic Shutter	Auto/Manual			
BLC	ON/OFF			
WDR	OFF/Dynamic Level Adjustment			
Video Adjustment	Brightness/Color/Saturation/Contrast/Sharpness/B/W mode/Gamma curve			
SNR	>55dB			
Effective Pixels	2.07m,16:9			
Pan-and-Tilt Parameter	Pan/Tilt Movement	-170°~+170°/-30°~+90°		
	Pan/Tilt Control Speed	0.1~60°/S; 0.1~30°/S		
	Preset Speed/Quantity	Pan:60°/S, Tilt:30°/S; Up to 255 preset positions (10 remote control)		
Audio Compression Format	AAC MP3 G.711A			
Video Compression Format	H.264 H.265 Dual Streaming Output			
Output Resolutions	720p25/29.97/30/50/59.94/60 1080p25/30/29.97/30/50/59.94/60			
Control Protocol	VISCA Pelco-D Pelco-P			
Baud Rate(bps)	115200 9600 4800 2400bps			
Network Protocol	RTSP RTMP ONVIF GB/T28181 VISCA			
Supported Standards	SDI SMPTE 425M (Level A & B) SMPTE 424M SMPTE 292M SMPTE 259M-C DVB-ASI			
Power	Input Voltage	DC12V/1.5A		
	Max Power	12W		
Environment	Temperature	-10℃~50℃		
	Humidity	20%~80%		
Physical	Weight	Net	1.4kg	
	Dimension	Net	180mm(front)×188mm(side)×198mm(height)	

