

RGBlink vue PTZ camera



Front View



Rear View



Left View

Key Features

- High speed optical zoom
- Low-Latency SRT Upload to Cloud
- High performance in low light scenarios with Wide Dynamic Range
- Full 1920x1080p HD Resolutions up to 60 frames per second
- H.265/H.264 Dual Stream Output Adapted to Different Network Environments
- Pan and Tilt Control
- Optional interface
- Optional 12X/20X/30X optical zoom
- NDI | HX output optional
- Wide Application
- Low-power Sleep Function
- Support TALLY
- Support PoE

Specification

Interface	Output	3G SDI	1xBNC		
		HDMI	1xHDMI-A		
		USB	1xUSB-A		
		LAN	1xRJ45		
	Audio	IN 1x3.5mm Stereo Jack			
	Control	RS232 IN/OUT	2xDIN8		
		RS485	1x4pin Terminal		
	Power	1xDC12V Jack			
Performance	Camera	Optical Zoom	f=4.1~49.2mm	20X f=5.5~110mm	30X f=5.2~148.4mm
		View Angle	6.57°~70.28°	3.45°~60.04°	2.14°~58.1°
		AV	F1.8 ~ F2.68	F1.6 ~ F3.5	F1.3 ~ F4.8
		Digital Zoom	10X		
		Minimum Illumination	0.5Lux (F1.8, AGC ON)		
		DNR	2D & 3D DNR		
		White Balance	Auto/Manual/One Push/3000K to 7000K(selectable)		
		Focus	Auto/Manual		
		Aperture/Electronic Shutter	Auto/Manual		
		BLC	ON/OFF		
	WDR	OFF/Dynamic Level Adjustment			
	Video Adjustment	Brightness/Color/Saturation/Contrast/Sharpness/B/W mode/Gamma curve			
	SNR	>55dB			
	Effective Pixels	2.07 megapixels			
	Sensor	1/2.8 inch HD CMOS Sensor			
	Pan-and-Tilt Parameter	Pan/Tilt Movement	-170°~+170°/-30°~+90°		
		Pan/Tilt Control Speed	0.1~60°/S; 0.1~30°/S		
Preset Speed/Quantity		Pan:60°/S, Tilt:30°/S; Up to 255 preset positions (10 remote control)			
360° TALLY		full 360° view of TALLY			
Audio Compression Format	AAC MP3 G.711A				
Video Compression Format	H.264 H.265 Dual Streaming Output				
Output Resolutions	1080p60/59.94/50/30/29.97/25 1080i60/59.94/50 720p60/59.94/50				
Control Protocol	VISCA Pelco-D Pelco-P ONVIF				
Baud Rate(bps)	115200 9600 4800 2400bps				
Network Protocol	RTSP RTMP ONVIF				
Supported Standards	SDI SMPTE 425M (Level A & B) SMPTE 424M SMPTE 292M SMPTE 259M-C DVB-ASI				
Power	Input Voltage	DC12V/1.5A			
	Max Power	12W			
Environment	Temperature	-10℃~50℃			
	Humidity	20%~80%			
Physical	Weight	Net	1.7kg		
	Dimension	Net	180mm(front)×188mm(side)×198mm(height)		

Order Codes

Product Code	Item
981-0011-27-0	RGB20X-POE-TLY
981-0011-28-0	RGB20X-PNDI-TLY
981-0011-29-0	RGB20X-USB-TLY
981-0011-31-0	RGB12X-POE-TLY
981-0011-32-0	RGB12X-PNDI-TLY
981-0011-33-0	RGB30X-POE-TLY
981-0011-34-0	RGB30X-PNDI-TLY

Tel: +86-592-5771197 | Fax: +86-592-5788216 | E-mail: sales@rgblink.com

Headquarter: Room 601A, No. 37-3 Banshang community, Building 3, Xinke Plaza, Torch Hi-Tech Industrial Development Zone, Xiamen, China

Specifications are correct at time of printing and subject to change or alteration without notice.

RGBlink[®]



www.rgblink.com