

PRELIMINARY

**RGBlink**<sup>®</sup>



## mini-mx

### Streaming Video Mixer

Mix to the max.

The all-in-one mini-mx video enables accessible professional multi-source video productions with cameras, laptops and multiple audio sources. For live presentation and streaming, do it all with ease from the unique and fully featured mini-mx.


mini-mx supports VISCA protocol for PTZ control. Control up four separate cameras with pan, tilt, zoom and focus.

The joystick provides tactile control for each PTZ camera. Used together toggle, set pan, tilt, zoom and focus from the front panel. Joystick and toggle are additionally dynamically assigned to settings including scale, position and crop for enhanced useability.


## Key Features

- 4K multi-channel streaming video mixer
- Built-in 5.5 inch touch screen for menu operation
- Quad HDMI 2.0 inputs, resolutions up to 4K@60
- Dual HDMI 1.3 outputs for monitoring of multi-window PVW and PGM
- Dual MIC In, Dual Audio Out for audio monitoring
- Mix for HDMI embedded and external audio
- One-key recording. Recording capacity of hard drive is up to 2T
- Stream to up to 4 platforms simultaneously over IP and 32 platforms via TAO APP
- Support multi-layer overlay, layer scaling and cropping
- 15 switch effect modes
- 5-direction joystick for controlling up to 4 PTZ cameras
- Save and store up to 16 scene presets. One-click for preset recall
- Control via computer and software
- Support Chroma Key
- One-key quick switch between portrait and landscape screen

## Application



## Dimension



## Specification

mini series    mini-mx

<b>Connectors</b>	Input	HDMI 4K	4×HDMI-A	
	Output	HDMI 2K	2×HDMI-A	
		USB (Recording)	1×USB-C	
		USB (Stream)	1×USB-C	
	Audio	IN	2×6.35mm XLR/6.35mm TRS Jack 1×6.35mm TRS Jack	
	OUT	1×6.35mm TRS Jack 1×3.5mm mini-Jack		
Communication	LAN	1×RJ45		
Power	Power Supply	1×USB-C		
<b>Performance</b>	Input Resolutions	SMPT	720p@50/60   1080i@50   1080p@23.98/24.97/50/59.94/60	
		VESA	1024×768@60   1280×720@60   1280×768@60   1280×800@60   1280×1024@60   1366×768@60   1366×768@60   1440×900@60   1600×1200@60   1680×1050@60   1920×1080@60   1920×1200@60   3840×2160@60   4096×2160@60	
	Output Resolutions	SMPT	720p@50/60   1080p@23.98/24.97/50/59.94/60	
		VESA	1024×768@60   1280×720@50/60   1280×768@60   1280×1024@60   1366×768@60   1920×1080@60	
	Video	Video Formats	HDMI 2.0   HDCP 2.2	
		Color Space	YUV2	
		Video Sampling	4:4:4 YUV	
		Video Latency	<4 frames	
	Audio	Line In Delay	up to 8 frames	
		Audio Format	HDMI	Linear PCM, 24 bits/48 kHz, 2 ch
		USB	Linear PCM, 16 bits/48 kHz, 2 ch	
Record/Storage	Record Formats	MP4   WAV		
	Disk Formats	FAT32(≤32 GB)   exFAT(64GB~2T)		
Supported Standards	HDMI	2.0		
	USB	3.0		
	H.265	ITU-T H.265/ ISO/IEC 23008-2		
<b>Power</b>	Compatibility	USB Power Delivery (PD) 3.0		
	Supported Cables	Certified USB PD Aware		
	Input Voltage	Type-C 12V/3A		
	Maximum Power	36W		
<b>Environment</b>	Temperature	0℃~45℃		
	Humidity	10%~85% RH		
<b>Physical</b>	Net Weight	TBC		
	Packaged Weight	TBC		
	Net Dimension	280mm × 222.6mm × 63.5mm		
	Packaged Dimension	332mm × 238.5mm × 109mm		

## Order Codes

Order Codes	Item
230-0004-01-0	mini-mx

## Contact us

Tel : +86-592-5771197  
 Fax : +86-592-5788216  
 E-mail : sales@rgblink.com

Headquarter: Room 601A, No. 37-3 Banshang community, Building 3,  
 Xinke Plaza, Torch Hi-Tech Industrial Development Zone, Xiamen, China

**RGblink**  
 www.rgblink.cn

