

IOX plus



**RGBlink**<sup>®</sup>

# ASK plus

ASK plus, 4K wireless HDMI extender, supports 4K60 resolution, super smooth playback with 100ms low latency.

This versatile extender supports wireless transmitter with two receivers without latency, which allows users to wireless stream the video content from one transmitter to two receivers simultaneously, excellent for applications like education or digital signage. Unique USB extension features allows touch panel to back control PC source.



4K60 high definition resolution



USB KVM function allow touch panel back control



As low as 100ms latency



one transmitter to multiple receivers



Equipped with the fast 802.11ac 2T2R WiFi MIMO module



Transmission distance up to 150 meters in the clear line of sight for 1\*RX, and 50 meters for 2\*RX



Auto channel selection



High-security protection

## Full Fidelity Video

Auto encode, transmission and decode preserves video quality, supporting full RGB color gamut without compression or artifacts

## Plug and play


Simply connect to HDMI port on laptop and remote display to project and mirror. Driver free and auto pairing, ASK nano is fast and simple to use.

## Wireless Displays Anywhere

Taking advantage of WiFi 5 (ac) and MIMO technologies, ASKplus transmitter and receivers devices pair automatically while providing for multicasting from HDMI sources. Connections are self-optimising for reliance and stability.

## High Performance Video

Direct HDMI signal connections make the most of high quality video signals and deliver low latency, lag and tear free video.



## Big Conference

1 transmitter multicast to 2 receivers over long distance




## Office presentation

KVM function allows presenters operate their laptop directly on a big touch panel display



## Public Signage

1 transmitter multicast to multiple receivers a perfect solution for public signage



## Specification



Interface	Input	TX	HDMI	1×HDMI-A	
	Output	TX	HDMI	1×HDMI-A	
		RX	HDMI	1×HDMI-A	
	Contro	TX	USB	1×Micro-USB (PC)	
			IR	1×IR	
	Power	RX	USB	2×USB (keyboard/mouse/touchpanel control cable)	
TX		Power	1×USB-C		
	RX	Power	1×USB-C		
Performance	Video Resolutions	SMPTE 4K@60   4K@30   4K@24   1080p@60/50/30/24   1080i@60/50   720p@60/50/30   480p			
	HDMI Version	HDMI	2.0	HDCP 2.1	
	Wireless Standard	IEEE 802.11b/g/n/ac, 2.4G/5GHz, 2T2R			
	Platform Supported	Any device that support HDMI port			
	Latency	About 100ms latency			
	Audio	Stereo, 44.1KHz			
	Distance	About 150 meters in the clear line of sight			
Power	Power Supply	TX	DC 5V/2A	RX	DC 5V/2A
	Power Consumption	TX	7W	RX	5W
Environment	Operating Temperature	0°C to +40°C (+32°F to +104°F)			
	Storage Temperature	-10°C to +60°C (+14°F to +140°F)			
	Operating Humidity	10% to 80% RH			
Physical	Net Dimension	TX	154*77.5*21mm	RX	154*77.5*21mm
	Net Weight	TX	330g	RX	330g

## Order Codes

Product Code	Item
450-3002-02-0	ASK plus 4K Wireless HDMI Extender (1*TX + 2*RX)

## Dimensions

Unit: mm



WEB: [www.rgblink.com](http://www.rgblink.com) EMAIL: [sales@rgblink.com](mailto:sales@rgblink.com) PHONE: +86 592 5771197  
Proudly designed and manufactured in Xiamen Hi Technology Zone, China

**RGBlink**<sup>®</sup>



[www.rgblink.com](http://www.rgblink.com)