



4K HDR Monitor


aura UHD 32 Gen 2

aura UHD 32 Gen 2 is broadcast -grade 4K HDR monitor, equipped with UHD (3840×2160) screen, supports quad link 12G SDI signal up to 8K input backward compatible with 4K@60Hz, supports high-precision 3D LUT with tetrahedral interpolation algorithm, supports HDR formats such as SMPTE ST2084(PQ), hybrid log-gamma HLG, various Gamma curves, camera Log and other professional functions which are widely used in film, television and advertisement industry.

Key Features

- Compared with the 1st generation, four 12G SDI signals can be monitored in quad-view at the same time. Window C is no longer limited to HDMI In 2 and USB-C
- Support HDR waveform
- ARRI and Red added to false color
- Under quad-view mode, each window has corresponding audio pillar
- Optimize energy saving, ESD, EMI circuit
- DC 24V XLR
- Support to install v mount battery plate
- Adopt panel of 1000nits brightness

Dimensions



Specification

Connectors	Input	12G-SDI	4 × BNC
		HDMI	2 × HDMI-A (*HDCP not supported)
		SFP	12G Fiber
Performance	Panel	Output	12G-SDI
			4 × BNC
		Size	31.5 inch
		Brightness	1000 cd/m2
		Type	QLED Panel
		Resolution	3840 × 2160
		Pixel Pitch	0.1369 (H) × 0.1369 (V) mm
		Aspect Ratio	16:9
		Backlight	LED
		Contrast Ratio	1000:1
		Color Depth	10bits(1.07B)
		Image Processing	12bits
		Response	9ms
		Viewing Angle	178°/178°
	Video Signal Format	SDI Signal Format	1080p@50/59.94/60; 1080p@23.98/24/25/29.97/30; 720p@50/59.94/60; 3840 × 2160p@23.98/24/25/29.97/30/50/59.94/60; 2048 × 1080p@23.98/24/25/29.97/30p/psf, 47.95/48/50/59.94/60p; 3840 × 2160p@24/25/30; 3840 × 2160p@24/25/30/50/60;
		HDMI Signal Format	720p@50/59.94/60;1080i@50/59.94/60; 1080p@23.98/24/25/29.97/30/50/59.94/60; 3840 × 2160p@23.98/24/25/29.97/30/50/59.94/60; 4096 × 2160p@23.98/24/25/29.97/30/50/59.94/60;
	Audio	Audio De-embedding Audio Meter Built-in Speaker Headphone	Support 16 channels (Up to 8 channels can be displayed simultaneously.) 1×8 ohm/0.5W Stereo mini Jack × 1
	General	Control/Update GPI Serial Port	1×RJ45 GPI1 -5, 1×RJ-45 RS-422, 2×RJ-45 (1 IN 1 OUT)
	Supported Standard	HDMI IN1	HDCP 1.X HDCP 2.2
		SDI	SMPTE -425M -A/B SMPTE -274M SMPTE -296M SMPTE ST 2036-1:2009 SMPTE ST 2048-2:2011 SMPTE ST 2081 SMPTE ST 2082
Power	Input Voltage	AC 100~240V 50/60Hz	
	Power Consumption (Max)	140W	
Environment	Operating Temperature	-10°C ~ 55°C (14°F to 155°F)	
	Operating Humidity	30% ~ 85%, RH	
	Storage Humidity	-20 ~ 60°C	
Physical	Net Weight	15.3kg	
	Packaged Weight	20.6kg	
	Net Dimension	751mm × 502mm × 179mm	
	Packaged Dimension	980mm × 270mm × 675mm	

Order Codes

Product Code	Item
410-3200-01-0	aura UHD 32 Gen 2
490-2000-02-0	V mount battery plate kit for aura UHD 27/32 Gen 2

Contact us

Tel: +86-592-5771197

Fax: +86-592-5788216

E-mail: sales@rgbink.com

Headquarter: Room 601A, No. 37-3 Banshang community, Building 3, Xinke Plaza,
Torch Hi-Tech Industrial Development Zone, Xiamen, China

RGBlink
www.rgbink.com

