

# 20X RGBlink vue PTZ camera



Front View



Rear View



Front View (Support NDI)

## Key Features

- High speed optical zoom
- RTSP/RTMP/SRT encoding output
- High performance in low light scenarios with Wide Dynamic Range
- Full 1920×1080p HD Resolutions up to 60 frames per second
- H.265/H.264 Dual Stream Output Adapted to Different Network Environments
- Pan and Tilt Control
- NDI | HX output for PNDI model camera
- Applicable to meeting, live streaming, church, classroom and more
- Low-power Sleep Function
- Support TALLY
- Support PoE

## Specification

Interface	Output	3G SDI HDMI USB LAN	1xBNC 1xHDMI-A 1xUSB-A 1xRJ45	
	Audio	IN	1x3.5mm Stereo Jack	
	Control	RS232 IN/OUT RS485	2xDIN8 1x4pin Terminal	
		Power		1xDC12V Jack
Performance	Camera	Optical Zoom View Angle AV Digital Zoom Minimum Illumination DNR White Balance Focus Aperture/Electronic Shutter BLC WDR Video Adjustment SNR Effective Pixels Sensor	20X f=4.8~96mm 3.45°~ 60.04° F1.8 ~ F2.9 10X 0.5Lux (F1.8, AGC ON) 2D & 3D DNR Auto/Manual/One Push/3000K to 7000K(selectable) Auto/Manual Auto/Manual ON/OFF OFF/Dynamic Level Adjustment Brightness/Color/Saturation/Contrast/Sharpness/B/W mode/Gamma curve >55dB 2.07 mega-pixel 1/2.8 inch HD CMOS	
	Pan-and-Tilt Parameter	Pan/Tilt Movement Pan/Tilt Control Speed Preset Speed/Quantity 360° TALLY	-170°~+170°/-30°~+90° 0.1~60°/S; 0.1~30°/S Pan:60°/S, Tilt:30°/S; Up to 255 preset positions (10 remote control) full 360° view of TALLY	
	Audio Compression Format	AAC   MP3   G.711A		
	Video Compression Format	H.264   H.265   Dual Streaming Output		
	Output Resolutions	1080p60/59.94/50/30/29.97/25   1080i60/59.94/50   720p60/59.94/50		
	Control Protocol	VISCA   Pelco-D   Pelco-P   ONVIF		
	Baud Rate(bps)	115200   9600   4800   2400bps		
	Network Protocol	RTSP   RTMP   ONVIF		
	Supported Standards	SDI SMPTE 425M (Level A & B)   SMPTE 424M   SMPTE 292M   SMPTE 259M-C   DVB-ASI		
	Power	Input Voltage	DC12V/1.5A	
		Max Power	12W	
	Environment	Temperature	-10℃~50℃	
		Humidity	20%~80%	
	Physical	Weight	Net 1.7kg	
Dimension		Net 180mm(front)×188mm(side)×198mm(height)		

## Order Codes

Product Code	Item
981-0011-76-0	RGB20X-PNDI-TLY, 20X NDI Camera with TALLY (Support PoE)
981-0011-77-0	RGB20X-PoE-TLY, 20X PTZ Camera with TALLY (Support PoE)

Tel: +86-592-5771197 | Fax: +86-592-5788216 | E-mail: sales@rgbblink.com

Headquarter: Room 601A, No. 37-3 Banshang community, Building 3, Xinke Plaza, Torch Hi-Tech Industrial Development Zone, Xiamen, China

Specifications are correct at time of printing and subject to change or alteration without notice.

**RGBlink**<sup>®</sup>  
www.rgbblink.com

