

12X RGBlink vue PTZ camera



Front View



Rear View



Front View (Support NDI)

Key Features

- High speed optical zoom
- Low-Latency SRT Upload to Cloud
- High performance in low light scenarios with Wide Dynamic Range
- Full 1920x1080p HD Resolutions up to 60 frames per second
- H.265/H.264 Dual Stream Output Adapted to Different Network Environments
- Pan and Tilt Control
- Optional interface
- NDI | HX output optional
- Wide Application
- Low-power Sleep Function
- Support TALLY
- Support PoE

Specification

Interface	Output	3G SDI	1xBNC
		HDMI	1xHDMI-A
		USB	1xUSB-A
		LAN	1xRJ45
	Audio	IN	1x3.5mm Stereo Jack
	Control	RS232 IN/OUT	2xDIN8
		RS485	1x4pin Terminal
	Power		1xDC12V Jack
Performance	Camera		12X
		Optical Zoom	f=4.1~49.2mm
		View Angle	6.57° ~ 70.28°
		AV	F1.8 ~ F2.68
		Digital Zoom	10X
		Minimum Illumination	0.5Lux (F1.8, AGC ON)
		DNR	2D & 3D DNR
		White Balance	Auto/Manual/One Push/3000K to 7000K(selectable)
		Focus	Auto/Manual
		Aperture/Electronic Shutter	Auto/Manual
		BLC	ON/OFF
		WDR	OFF/Dynamic Level Adjustment
		Video Adjustment	Brightness/Color/Saturation/Contrast/Sharpness/B/W mode/Gamma curve
		SNR	>55dB
		Effective Pixels	2.07 megapixels
		Sensor	1/2.8 inch HD CMOS
	Pan-and-Tilt Parameter	Pan/Tilt Movement	-170°~+170°/-30°~+90°
		Pan/Tilt Control Speed	0.1~60°/S; 0.1~30°/S
		Preset Speed/Quantity	Pan:60°/S; Tilt:30°/S; Up to 255 preset positions (10 remote control)
		360° TALLY	full 360° view of TALLY
	Audio Compression Format	AAC MP3 G.711A	
	Video Compression Format	H.264 H.265 Dual Streaming Output	
	Output Resolutions	1080p60/59.94/50/30/29.97/25 1080i60/59.94/50 720p60/59.94/50	
	Control Protocol	VISCA Pelco-D Pelco-P ONVIF	
	Baud Rate(bps)	115200 9600 4800 2400bps	
	Network Protocol	RTSP RTMP ONVIF	
	Supported Standards	SDI SMPTE 425M (Level A & B) SMPTE 424M SMPTE 292M SMPTE 259M-C DVB-ASI	
Power	Input Voltage	DC12V/1.5A	
	Max Power	12W	
Environment	Temperature	-10℃ ~ 50℃	
	Humidity	20%~80%	
Physical	Weight	Net	1.7kg
	Dimension	Net	180mm(front)×188mm(side)×198mm(height)

Order Codes

Product Code	Item
981-0011-74-0	RGB12X-PNDI-TLY, 12X NDI Camera with TALLY (Support PoE)
981-0011-75-0	RGB12X-PoE-TLY, 12X PTZ Camera with TALLY (Support PoE)

Tel: +86-592-5771197 | Fax: +86-592-5788216 | E-mail: sales@rgbink.com

Headquarter: Room 601A, No. 37-3 Banshang community, Building 3, Xinke Plaza, Torch Hi-Tech Industrial Development Zone, Xiamen, China

Specifications are correct at time of printing and subject to change or alteration without notice.

RGBlink
www.rgbink.com

